



Safety for Industrial Process

Physelec Family

SG

6-mm signal conditioner



Characteristics*

- Complete range of signal conditioners
- 6.2 mm thick and only 3.1 mm per channel for the two-channel versions
- High accuracy and repeatability < 0.1% of full scale
- Power supply on rail or via connectors
- Simplified configuration by DIP switches or USB using GEORGINSet software
- Diagnostic LED on the front panel for easy maintenance
- Insulation >3KV between input, output, and power supply in accordance with the EN 61140 standard
- Low consumption (0.8 W to 1.2 W)
- Five-year guarantee

* According to model

APPLICATIONS

- Water market
- Energy
- Metallurgy
- Cement works
- Chemicals & petrochemicals



www.georgin.com





Physelec Family

SG 6-mm signal conditioners

A complete range

■ **GT 45000** programmable by DIP/USB

Temperature transmitter for standard Pt, Ni, KTY and TC sensors, mV and R measurement, and potentiometer

■ **GS 75000**

Shunt resistance isolation amplifier / voltages in mV
Isolation and conversion of low-voltage bipolar and unipolar signals

■ **GN 25000**

Isolation amplifier
Isolation and conversion of standard signals

■ **GN 21000**

Signal separator / repeater
Isolation, conversion and loop powering of standard signals with two outputs

■ **GH 11000** (1 channel) and **GH 11020** (2 channels)

Isolator powered by the loop
Standard signal separation 0(4) ... 20 mA

■ **GC 52500**

HART transmitter power supply
Power supply and isolation of SMART transmitters with HART connection

■ **GC 52100**

Transmitter power supply
Power supply and isolation of two- and three-wire transmitters

■ **GB 64000**

Bipolar isolation amplifier
Isolation and conversion of standard industrial bipolar and unipolar signals



Operating voltage

Up to 600 V AC/DC for overvoltage category II

Protection from electric shock

Separation of protection by reinforced insulation in compliance with EN 61010 Part 1 up to 300 V AC/DC for overvoltage category II

Operating temperature

Operation from -25°C to +70°C

Electrical power supply

16.8 V to 31.2 V DC

EMC

EN 61326-1



For more information,
please download our technical data sheets
from www.georgin.com.

pl-sg-en-27-01-2015

